

The diagram illustrates a symmetrical drainage channel cross-section. Key features include:

- Slopes:** Side slopes are indicated as 1:1.5.
- Dimensions:**
 - Total width at the top: 300
 - Channel bottom width: 180
 - Channel depth: 20
 - Side slope length: 120
 - Top width of side slope: 210
 - Bottom width of side slope: 30
- Materials and Layers:**
 - DRN TL. 10 cm (Drainage layer, 10 cm thick)
 - KAMEN. DLAŽBA TL. 25 cm (Stone paving, 25 cm thick)
 - DO ŠTĚRKOPÍSKU TL. 10 cm (To the gravel-sand layer, 10 cm thick)
 - PATEK Z LON. KAMENE 30/40 (Gravel pit made of rounded stones 30/40 mm)
 - DUBANÝ PAKADAN TL. 20 cm (Layered bedding, 20 cm thick)
 - EFEKTIVNÍ ŽRNO d 7cm (Effective grain size 7 cm)
- Other Labels:** "OSEŤI" (Slopes) are labeled on both sides.

1:1.5

OSEŤ!

DRN TL. 10 cm

KAP. DLAŽBA TL. 25 cm

DO ŠTĚRKOPISKU TL. 10 cm

210

90

180

30

20

10

25

30

30

30

30

40

1:1.5

OSEŤ!

PATKA Z LOP. KAPENE 30/40

DLISANÝ POKADAN TL. 20 cm

EFEKTIVNÍ ZBNO Ø 7 cm