


Obecně, v případě odkrytí fragmentů původních povrchů, budou tyto ponechány dodavatelem bez dalšího zásahu, do rozhodnutí investora o dalším postupu.

-
- Výřez z půdorysu 1. nádvoří
- travnatá plocha
- štěrk
- šotolinový chodník
- dešťový svod
- elektrický rozvaděč
- studna
- nikla
- pumpa
- vstup
- OBNAŽENÁ ZEMÍČÍ
- TYČ (1KS)
- vstup
- dešťový svod
- studna
- nikla
- 379.89 ± 225
- 379.82 ± 218
- 379.81 ± 215
- 379.77 ± 214
- 379.75 ± 213
- 379.67 ± 222
- 379.68 ± 221
- 379.76 ± 220
- 379.68 ± 223
- 379.77 ± 222
- 379.67 ± 223
- 379.84 ± 228
- 379.75 ± 187
- 379.75 ± 186
- 379.75 ± 185
- 379.75 ± 184
- 379.75 ± 183
- 379.75 ± 182
- 379.75 ± 181
- 379.75 ± 180
- 379.75 ± 179
- 379.75 ± 178
- 379.75 ± 177
- 379.75 ± 176
- 379.75 ± 175
- 379.75 ± 174
- 379.75 ± 173
- 379.75 ± 172
- 379.75 ± 171
- 379.75 ± 170
- 379.75 ± 169
- 379.75 ± 168
- 379.75 ± 167
- 379.75 ± 166
- 379.75 ± 165
- 379.75 ± 164
- 379.75 ± 163
- 379.75 ± 162
- 379.75 ± 161
- 379.75 ± 160
- 379.75 ± 159
- 379.75 ± 158
- 379.75 ± 157
- 379.75 ± 156
- 379.75 ± 155
- 379.75 ± 154
- 379.75 ± 153
- 379.75 ± 152
- 379.75 ± 151
- 379.75 ± 150
- 379.75 ± 149
- 379.75 ± 148
- 379.75 ± 147
- 379.75 ± 146
- 379.75 ± 145
- 379.75 ± 144
- 379.75 ± 143
- 379.75 ± 142
- 379.75 ± 141
- 379.75 ± 140
- 379.75 ± 139
- 379.75 ± 138
- 379.75 ± 137
- 379.75 ± 136
- 379.75 ± 135
- 379.75 ± 134
- 379.75 ± 133
- 379.75 ± 132
- 379.75 ± 131
- 379.75 ± 130
- 379.75 ± 129
- 379.75 ± 128
- 379.75 ± 127
- 379.75 ± 126
- 379.75 ± 125
- 379.75 ± 124
- 379.75 ± 123
- 379.75 ± 122
- 379.75 ± 121
- 379.75 ± 120
- 379.75 ± 119
- 379.75 ± 118
- 379.75 ± 117
- 379.75 ± 116
- 379.75 ± 115
- 379.75 ± 114
- 379.75 ± 113
- 379.75 ± 112
- 379.75 ± 111
- 379.75 ± 110
- 379.75 ± 109
- 379.75 ± 108
- 379.75 ± 107
- 379.75 ± 106
- 379.75 ± 105
- 379.75 ± 104
- 379.75 ± 103
- 379.75 ± 102
- 379.75 ± 101
- 379.75 ± 100
- 379.75 ± 99
- 379.75 ± 98
- 379.75 ± 97
- 379.75 ± 96
- 379.75 ± 95
- 379.75 ± 94
- 379.75 ± 93
- 379.75 ± 92
- 379.75 ± 91
- 379.75 ± 90
- 379.75 ± 89
- 379.75 ± 88
- 379.75 ± 87
- 379.75 ± 86
- 379.75 ± 85
- 379.75 ± 84
- 379.75 ± 83
- 379.75 ± 82
- 379.75 ± 81
- 379.75 ± 80
- 379.75 ± 79
- 379.75 ± 78
- 379.75 ± 77
- 379.75 ± 76
- 379.75 ± 75
- 379.75 ± 74
- 379.75 ± 73
- 379.75 ± 72
- 379.75 ± 71
- 379.75 ± 70
- 379.75 ± 69
- 379.75 ± 68
- 379.75 ± 67
- 379.75 ± 66
- 379.75 ± 65
- 379.75 ± 64
- 379.75 ± 63
- 379.75 ± 62
- 379.75 ± 61
- 379.75 ± 60
- 379.75 ± 59
- 379.75 ± 58
- 379.75 ± 57
- 379.75 ± 56
- 379.75 ± 55
- 379.75 ± 54
- 379.75 ± 53
- 379.75 ± 52
- 379.75 ± 51
- 379.75 ± 50
- 379.75 ± 49
- 379.75 ± 48
- 379.75 ± 47
- 379.75 ± 46
- 379.75 ± 45
- 379.75 ± 44
- 379.75 ± 43
- 379.75 ± 42
- 379.75 ± 41
- 379.75 ± 40
- 379.75 ± 39
- 379.75 ± 38
- 379.75 ± 37
- 379.75 ± 36
- 379.75 ± 35
- 379.75 ± 34
- 379.75 ± 33
- 379.75 ± 32
- 379.75 ± 31
- 379.75 ± 30
- 379.75 ± 29
- 379.75 ± 28
- 379.75 ± 27
- 379.75 ± 26
- 379.75 ± 25
- 379.75 ± 24
- 379.75 ± 23
- 379.75 ± 22
- 379.75 ± 21
- 379.75 ± 20
- 379.75 ± 19
- 379.75 ± 18
- 379.75 ± 17
- 379.75 ± 16
- 379.75 ± 15
- 379.75 ± 14
- 379.75 ± 13
- 379.75 ± 12
- 379.75 ± 11
- 379.75 ± 10
- 379.75 ± 9
- 379.75 ± 8
- 379.75 ± 7
- 379.75 ± 6
- 379.75 ± 5
- 379.75 ± 4
- 379.75 ± 3
- 379.75 ± 2
- 379.75 ± 1
- 379.75 ± 0

The drawing illustrates a drainage system layout with two main sections. Key features include:

- Left Section:** Starts with a manhole (líc nily) at elevation 379.67. A pump (pumpa) is located at elevation 379.84. The channel (koryto) is shown with a slope of 1/69. The distance between the manhole and the pump is 169 units.
- Right Section:** Features a manhole (líc budovy) at elevation 379.53. A pump (pumpa) is located at elevation 379.84. The channel (koryto) is shown with a slope of 1/69. The distance between the manhole and the pump is 169 units.
- Central Section:** A road section (dlážděná cesta) with a width of 2898 units. It is flanked by grassy areas (travnaté plochy) with a width of 1014 units. The road is shown with a slope of 1/69.
- Right Section:** A road section (dlážděná cesta) with a width of 2898 units. It is flanked by grassy areas (travnaté plochy) with a width of 1014 units. The road is shown with a slope of 1/69.
- Labels:** The drawing includes labels for "travnatá plocha netvoří ideální rovinu" (grass area does not form an ideal plane) and "vysvahování od koryt je nepravidelné" (sloping away from the channel is irregular).
- Scale:** A scale bar is provided at the bottom right, indicating a distance of 379.00 units.



ZODP. PROJEKTANT	STAVEBNÍ ČÁST	ING.ARCH.MILAN ŠINDLER IPD SERVIS PROJEKČNÍ KANCELÁŘ Domanín 106,379 01 Třeboň TEL.777 178440 ICO : 135 01 402	
Ing. arch. Milan Šindler	Daniël Paštyka		
INVESTOR	NÁRODNÍ ZEMĚDĚLSKÉ MUZEUM, s.p.o., Kostelní 1300/44, Praha 7		
STAVBA A NÁZEV OBJEKTU	NZM OHRADA ODVODNĚNÍ DEŠŤOVÝCH VOD A ÚPRAVA 1. NÁDVORÍ	DATUM	03/2020
		STUPEŇ	DPS
NÁZEV VÝKRESU	PŮDORYS A PODÉLNÝ ŘEZ D-D, STŘEDNÍ ČÁSTI NÁDVORÍ STÁVAJÍCÍ STAV + BOURACÍ PRÁCE	ČÍS. ZAK.	
		MĚŘÍTKO 1:100	ČÍS. VÝKR. D.1.1. 214